

PERFORMANCE VICTORY 15W-40



Mineral lubricant suitable for on-road diesel engines.

APPLICATIONS

- ELF PERFORMANCE VICTORY 15W-40 is a mineral lubricant used in on-road diesel technology.
- It is recommended to Euro 3, and previous engines of most European and American manufacturers. It is also adapted to Euro 5 and previous engines of some manufacturers with appropriate oil drain intervals.
- ELF PERFORMANCE VICTORY 15W-40 enables coverage some fleet of mixed brands (American and European manufacturers) with a minimal number of products.

APPROVALS

Specifications API CI-4/CH-4/SL ACEA E7

Manufacturers' approval Cummins CES 20077/78

Mack EO-N MAN M 3275 MB-Approval 228.3 Renault Trucks RLD-2 Volvo VDS-3

Meets the requirements of CATERPILLAR ECF-1a

DAF IVECO SCANIA ISUZU

PERFORMANCES AND CUSTOMER BENEFITS

- ELF PERFORMANCE VICTORY 15W-40 contains excellent viscosity stability in service, guaranteeing effective engine lubrication in severe conditions.
- Outstanding detergent, dispersant and anti-wear properties keep the engine clean and enable efficient control of soot, sludge and piston deposits.
- Piston cleanliness performance affords effective protection against cylinder liner polishing.

PHYSICAL AND CHEMICAL CHARACTERISTICS

| ELF PERFORMANCE VICTORY 15W-40 | | Method | Value |
|--------------------------------|---------|------------|-------|
| Density at 15°C | kg/m³ | ASTM D1298 | 888 |
| Kinematic Viscosity at 40°C | mm²/s | ASTM D445 | 98.7 |
| Kinematic Viscosity at 100°C | mm²/s | ASTM D445 | 13.4 |
| Viscosity Index | - | ASTM D2270 | 136 |
| Flash point | °C | ASTM D92 | 236 |
| Pour Point | °C | ASTM D97 | -30 |
| T.B.N | mgKOH/g | ASTM D2896 | 11 |
| Sulphated Ash | % m/m | ASTM D874 | 1.45 |

The features mentioned above are average values obtained with some variability in production and do not constitute a specification.



ELF PERFORMANCE VICTORY 15W-40 Update : 04/2015

