



DYNATRANS FD-1

50 – 60



Lubricants for **axles** and **final drives** of earth moving and mining machineries.

SPECIFICATIONS

Meets the requirements of

- ✓ Caterpillar FD-1 specification

APPLICATIONS

TOTAL DYNATRANS FD-1 50 – 60 is suitable in **axles** and **final drives** for which the manufacturer recommends a **fluid meeting the CATERPILLAR FD-1 specification**.

This lubricant must not be used in specific organs equipped with friction discs like self-locking differentials or oil immersed brake systems.

For CATERPILLAR equipment:

- SAE 50 grade can be used up to + 30°C
- SAE 60 grade can be used up to + 50°C

TOTAL DYNATRANS FD-1 50 – 60 is particularly recommended in **final drives** of **machines working** under severe conditions of heavy load and high temperature.

PERFORMANCES AND CUSTOMER BENEFITS

- Provides the best protection to mechanical parts of final drive organs
- Provides an improved durability of the material within extended drain intervals

PHYSICAL AND CHEMICAL CHARACTERISTICS*

TOTAL DYNATRANS FD-1		Method	50	60
Kinematic Viscosity at 40°C	mm ² /s	ASTM D445	210	341
Kinematic Viscosity at 100°C	mm ² /s	ASTM D445	18.5	26
Viscosity Index	-	ASTM D2270	98	100
Pour Point	°C	ASTM D97	-24	-15

* The features mentioned above are average values obtained with some variability in production and do not constitute a specification.

TOTAL LUBRIFIANTS

562, avenue du Parc de l'Île
92029 Nanterre cedex
FRANCE

TOTAL DYNATRANS FD-1 50 – 60

Update 12/2014

www.lubricants.total.com



This lubricant does not cause adverse health effects when used in the intended application.
A safety datasheet is accessible on request from your local dealer or on the website www.quickfds.com