

# FLUIDMATIC DVI MV

Automatic Transmission Fluid

## KEY DATA

### MANUFACTURER APPROVALS<sup>1</sup>:

- Mercedes-Benz MB-Approval 236.2



### MEETS THE REQUIREMENTS<sup>1</sup>:

- Honda DW-1
- Aisin Warner JWS 3324
- JWS 3309, AW-1
- Toyota Type WS
- JASO 1A (M315)
- Hyundai-Kia NWS-9638
- SP-IV / SP-IV-RR / SPHIV

### SUITABLE FOR:

- Bentley : P/N PY112995PA
- Audi/Volkswagen : G 052 025-A2, G053 025-A2, G 052 162 (-A1/-A2), G055 025 A2, G 052 162, G 055 162 (-A2/-A6), G 060 162, G 052 990, G 055 540 (A2)
- BMW/Mini
- Chrysler/Dodge/Jeep : P/N 05127382AA, 68043742AA, 68171866AA
- Ford/Lincoln

<sup>1</sup> Please refer to car owner's manual

## TECHNOLOGY

### Life-boost technology

**Your peace of mind solution.**

*Life-boost technology will maximize the durability of the components and parts of the driveline equipment of your vehicle.*

Our products will offer the best services as your vehicle will require drastically less maintenance providing reduced Total Cost Ownership (TCO) with on top a significant extended drain interval. **A solution which offer a peace of mind throughout the normal lifetime of your vehicle.**



## APPLICATIONS

FLUIDMATIC DVI MV is an innovative automatic transmission fluid based on an advanced synthetic technology allowing very high performances. This fluid is Approved DEXRON® VI.

This lubricant has been developed to meet the needs of modern transmission where higher efficiency is required. It is a low viscosity formulation that meets the more demanded OEM specifications.

FLUIDMATIC DVI MV is recommended for use in the latest generation of high efficiency 6-speed automatic transmissions with longer fluid life capabilities and heavier load capacities.

## CUSTOMERS BENEFITS

- Exceptional friction and anti-shudder performances: FLUIDMATIC DVI MV provides consistent shift performance for the life of the transmission.
- Excellent viscosity stability in operation: FLUIDMATIC DVI MV has been properly formulated to remain shear stable over time providing extended life time of the fluid.
- Fuel economy: Its formulation and excellent low temperature performance provide intended fuel economy benefits.
- Outstanding film-strength and anti-wear properties which provide a perfect lubrication all over time and protection of the transmission.
- Enhanced thermal stability and oxidation resistance: Its high quality synthetic base oils and superior anti-oxidant and detergent additives provide a very good oxidation control of the fluid over time even in very severe conditions.
- Protects transmission gears and allows them operate smoothly.
- Excellent parts material compatibility.

## CHARACTERISTICS<sup>2</sup>

TEST	UNIT	TEST METHOD	RESULT
Viscosity grade	-	-	154
Kinematic viscosity at 40°C	mm <sup>2</sup> /s	ASTM D445	29
Kinematic viscosity at 100°C	mm <sup>2</sup> /s	ASTM D445	5.9
Viscosity Index	-	ASTM D2270	154
Flashpoint	°C	ASTM D92	208
Pour point	°C	ASTM D97	-45
Density	Kg/m <sup>3</sup>	DIN 51757 D	845

<sup>2</sup> The characteristics given above are obtained with a standard tolerance threshold during production and may not be considered specifications.

## RECOMMENDATIONS FOR USE

Before using the product, the vehicle's maintenance guide should be checked. Oil changes should be carried out in accordance with the manufacturer's recommendations. The product should not be stored at temperatures over 60°C.

It should be kept away from sunlight, intense cold and extreme temperature fluctuations. If possible, the packaging should not be exposed to the elements. Otherwise, the drums should be laid horizontally in order to avoid any contamination from water and to prevent the product's label from rubbing off.

## HEALTH, SAFETY AND THE ENVIRONMENT

Based on the toxicological information available, this product should not cause any adverse health effects, provided it is used for its intended purpose and in accordance with the recommendations laid out in the Safety Data Sheet (SDS).

This can be obtained on request from your local reseller and is available for consultation at <http://sdstotalms.total.com>. This product should not be used for any purposes other than the ones for which it is intended.

TOTAL LUBRIFIANTS – Immeuble Spazio  
562, avenue du Parc de l'île  
92029 Nanterre cedex  
France

**FLUIDMATIC DVI MV**  
Last update of this datasheet: 02/2021

Some variations can be expected under normal production conditions, but these should not affect the product's expected performance irrespective of the site. The information contained in this document is subject to change without notice. Our products can be viewed on our website at [www.lubricants.total.com](http://www.lubricants.total.com).