

NEPTUNA 2T RACING

Gasoline engine oil

KEY DATA



✓ Leisure crafts

SPECIFICATIONS AND APPROVALS

International Specifications:

API TC
NMMA TC-W3®

Suitable for:

- ✓ BOMBARDIER
- ✓ EVINRUDE
- ✓ JOHNSON
- ✓ KAWASAKI
- ✓ MARINER
- ✓ MERCURY
- ✓ SEA-DOO
- ✓ SUZUKI
- ✓ TOHATSU
- ✓ YAMAHA
- ✓ etc.

APPLICATIONS

TOTAL NEPTUNA 2T RACING is a **high-performance** lubricant suitable for **2 strokes gasoline engines** running at high engine speed.

It is adapted to all 2 strokes engines, including **direct injection engines**.

The mixing with the fuel should be in accordance with the manufacturer's recommendations.

PERFORMANCES AND CUSTOMER BENEFITS

TOTAL NEPTUNA 2T RACING resists to **high pressures and temperatures** of modern engines. Its enhanced lubrication **reduces wear**.

Its optimized viscosity facilitates mixture with gasoline and produces a **homogeneous and stable pre-mix**, even at low temperature. It also can be used for in-line mixing.

TOTAL NEPTUNA 2T RACING has good ability to **complete combustion**, ensuring exhaust deposits and smoke reduction.

Outstanding detergent and dispersant properties keep the engine clean and guarantee extended engine lifespan.

Its **anti-corrosion properties** protect engine internal components.

NEPTUNA 2T RACING

Gasoline engine oil

PHYSICAL AND CHEMICAL CHARACTERISTICS*

TEST	UNIT	TEST METHOD	VALUE
Density at 15 °C	kg/m ³	ASTM D1298	866
Kinematic Viscosity at 40 °C	mm ² /s	ASTM D445	57
Kinematic Viscosity at 100 °C	mm ² /s	ASTM D445	9
Viscosity Index	-	ASTM D2270	136
Pour Point	°C	ASTM D97	-36
Color	-	-	Blue-green

* The features mentioned above are average values obtained with some variability in production and do not constitute a specification.

RECOMMENDATIONS FOR USE

Before using the product, it is important to check the service manual of the vehicle: the drain is carried out according to the manufacturer's requirements.

The product should not be stored at a temperature above 60 °C.

Exposure to strong sunlight, extreme cold or high temperature variations must be avoided. All packages should be protected from bad weather conditions.

The drums should be stored horizontally to avoid a possible contamination by water and the damage of the product label.

HEALTH, SAFETY AND THE ENVIRONMENT

Based on available information, this product does not cause adverse health effects when used in the intended application and the recommendations provided in the Safety Data Sheet (MSDS) are followed.

It is accessible on request from your local dealer or on the website <https://sdstotalms.total.com>.

This product should not be used for applications other than those for which it is intended. If disposing of used product, take care to protect the environment and comply with local regulations.