

TRAXIUM AXLE 8 75W-90

Transmission Oil

KEY DATA

SYNTHETIC BASED OIL FOR GEARS

INTERNATIONAL STANDARDS

SAE 75W-90

API GL-5

Applications

TOTAL TRAXIUM AXLE 8 75W-90 is synthetic based oil designed for the lubrication of all gear boxes and axles requiring an **API GL-5 level** and a viscosity of **SAE 75W-90**.

Customer benefits

- Reduced cost of maintenance: specially formulated to reach the drain intervals recommended by the manufacturer.
- Improved protection of axles against wear and corrosion due to extreme-pressure properties of oil.
- **Improved driver start up experience**: low temperature fluidity due to a high viscosity index, generating benefits during cold starts and limiting drag losses and fuel consumption.
- Improved stability in operation due to high viscosity index
- High compatibility with oil filters due to antifoam properties

Characteristics*

Test	Unit	Test method	Result
Volumetric mass at 15°C	kg/m ³	DIN 51757 D	884
Viscosity at 40°C	mm²/s	ASTM D445	106
Viscosity at 100°C	mm²/s	ASTM D445	17
Viscosity index	-	ASTM D2270	175
Pour point	°C	ASTM D97	-39
Flash point	°C	ASTM D92	210

* The characteristics given above are obtained with a standard tolerance threshold during production and may not be considered specifications.

Recommendations for use

Before using the product, the vehicle's maintenance guide should be checked. Oil changes should be carried out in accordance with the manufacturer's recommendations.

The product should not be stored at temperatures over 60°C. It should be kept away from sunlight, intense cold and extreme temperature fluctuations.

If possible, the packaging should not be exposed to the elements. Otherwise, the drums should be laid horizontally in order to avoid any contamination from water and to prevent the product's label from rubbing off.

Health, safety and the environment

Based on the toxicological information available, this product should not cause any adverse health effects, provided it is used for its intended purpose and in accordance with the recommendations laid out in the Safety Data Sheet. This can be obtained on request from your local reseller and is available for consultation at <u>www.quickfds.fr</u>.

This product should not be used for any purposes other than the ones for which it is intended.

When disposing of the product after use, please protect the environment and comply with local regulations.

