

TRAXIUM GEAR 6 75W-85

Transmission Oil

KEY DATA

TRANSMISSION GEAR OIL

SAE 75W-85



INTERNATIONAL STANDARDS

- API GL-4

SUITABLE FOR¹

- KIA, Hyundai, Nissan, Mitsubishi, Suzuki, Daewoo, Daihatsu.
- Car Manufacturers requesting 75W-85 SAE Grades.

¹ Please refer to car owner's manual

APPLICATIONS

TRAXIUM GEAR 6 75W-85 is designed for synchronized gear boxes requesting API GL-4 level.

TRAXIUM GEAR 6 75W-85 is particularly suitable for gear boxes of Asian car manufacturers requesting 75W-85.

CUSTOMERS BENEFITS

- Efficient protection of gears against wear and corrosion due to stable extreme-pressure properties.
- High compatibility with oil filters due to antifoam properties.
- Efficient stability in operation.

CHARACTERISTICS²

TEST	UNIT	TEST METHOD	RESULT
Viscosity grade	-	-	75W-85
Kinematic viscosity at 40°C	mm ² /s	ASTM D445	80
Kinematic viscosity at 100°C	mm ² /s	ASTM D445	13.2
Viscosity Index	-	-	-
Flashpoint	°C	ASTM D92	>200
Pour point	°C	ASTM D97	-42
Density	Kg/m ³	DIN 51757 D	842
Brookfield Viscosity at -40°C	mPa/s	-	< 146 000

² The characteristics given above are obtained with a standard tolerance threshold during production and may not be considered specifications.

RECOMMENDATIONS FOR USE

Before using the product, the vehicle's maintenance guide should be checked. Oil changes should be carried out in accordance with the manufacturer's recommendations.

The product should not be stored at temperatures over 60°C.

It should be kept away from sunlight, intense cold and extreme temperature fluctuations.

If possible, the packaging should not be exposed to the elements. Otherwise, the drums should be laid horizontally in order to avoid any contamination from water and to prevent the product's label from rubbing off.

HEALTH, SAFETY AND THE ENVIRONMENT

Based on the toxicological information available, this product should not cause any adverse health effects, provided it is used for its intended purpose and in accordance with the recommendations laid out in the Safety Data Sheet.

This can be obtained on request from your local reseller and is available for consultation at www.quickfds.fr.

This product should not be used for any purposes other than the ones for which it is intended.

TOTAL LUBRIFIANTS – Immeuble Spazio
562, avenue du Parc de l'île
92029 Nanterre cedex
France

TRAXIUM GEAR 6 75W-85
Last update of this datasheet: 10/2020

Some variations can be expected under normal production conditions, but these should not affect the product's expected performance irrespective of the site. The information contained in this document is subject to change without notice. Our products can be viewed on our website at www.lubricants.total.com.