

PROSYLVA CHAIN EXTREM

Chainsaw oil

KEY DATA



✓ CHAINSAW

Loss lubrication of chainsaw and high speed machinery.

Suitable for:

STIHL, HUSQVARNA, ECHO, DOLMAR, MAKITA, McCULLOCH,
RYOBI, GT GARDEN, VOLTOR, etc

APPLICATIONS

TOTAL PROSYLVA CHAIN EXTREM is dedicated to all **high speed machineries**: manual or mechanical chainsaw, chain conveyors.

This lubricant is adapted to **all wood transformation**.

TOTAL PROSYLVA CHAIN EXTREM is particularly recommended for **manual chainsaw** of woodcutter and also for **industrial conveyors**.

PERFORMANCES AND CUSTOMER BENEFITS

TOTAL PROSYLVA CHAIN EXTREM has very **adhesive behaviour** which reduces spattering and guarantees the lubrication on the entire length of the moving chain.

TOTAL PROSYLVA CHAIN EXTREM exhibits lots of **properties**:

- ✓ Reinforced anti-wear additivation
- ✓ Improved anti-rust property
- ✓ Friction reduction
- ✓ Chain and guide wear reduction
- ✓ Spattering, pollution and oil consumption reductions

PROSYLVA CHAIN EXTREM

Chainsaw oil

PHYSICAL AND CHEMICAL CHARACTERISTICS*

TEST	UNIT	TEST METHOD	RESULT
Density at 15 °C	kg/m ³	ASTM D1298	884
Kinematic Viscosity at 40 °C	mm ² /s	ASTM D445	220
Pour Point	°C	ASTM D97	-9
Behavior	-	-	Adhesive

* The features mentioned above are average values obtained with some variability in production and do not constitute a specification.

RECOMMENDATIONS FOR USE

Before using the product, the equipment's maintenance guide should be checked. Oil changes should be carried out in accordance with the manufacturer's recommendations.

The product should not be stored at temperatures over 60°C. It should be kept away from sunlight, intense cold and extreme temperature fluctuations.

If possible, the packaging should not be exposed to the elements. Otherwise, the drums should be laid horizontally in order to avoid any contamination from water and to prevent the product's label from rubbing off.

HEALTH, SAFETY AND THE ENVIRONMENT

Based on the toxicological information available, this product should not cause any adverse health effects, provided it is used for its intended purpose and in accordance with the recommendations laid out in the Safety Data Sheet. This can be obtained on request from your local reseller and is available for consultation at <http://sdstotalms.total.com>.

This product should not be used for any purposes other than the ones for which it is intended.